



Chain Sling CSX-276 Grade 10

Product information

Design: Chain sling with master link on one end and clevis safety hooks on the other ends.
 Ø 19 and 22 mm chain are fitted with eye safety hooks. Other combinations possible on demand.

Dimensions: Ø 6–22 mm (other dimensions on demand).

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C (up to 380° possible on demand)

Standard: EN 818-4

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Part Code

WLL
ton

2409

2

2409

2

2409

2

2409

2

2409

2

2409

2

2409

2

2409

2

2409

2

2409

2.65

2409

2.65

2409

2.65

2409

2.65

2409

2.65

2409

2.65

2409

2.65

2409

2.65

2409

2.65

2409

3.55

2409

3.55

2409

3.55

2409

3.55

2409

3.55

2409

3.55

2409

3.55

2409

3.55

2409

3.55

2409

5.6

2409

5.6

2409

5.6

148963

14

2409

20

2409

20

2409

20

2409

20

2409

20

2409

20

2409

20

2409

20

148964

20

2409

26.5

2409

26.5

2409

26.5

2409

26.5

2409

26.5

2409

26.5

2409

26.5

2409

26.5

2409

26.5