



Welded Master Link X-002W

Product information

- Welded Master Link designed for 1-2 legs Wire Rope and Chain Slings.
- At least 25% greater WLL than traditional Grade 8 products.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Part code	Code	WLL ton	For chain gr 10 Ø 2 leg mm	For chain gr 10 Ø 1 leg mm	Din 15401.NO	D mm	A mm	B mm	Weight kg
402100280500	CD-13	2.8	6	7,8	4	13	120	70	0.4
402100400500	CD-16	4	7,8	10	5	16	140	80	0.7
402100670500	CD-19	6.7	10	13	6	19	160	95	1.1
402100850500	CD-22	8.5	10	13	10	22	170	105	1.6
402101150500	CD-28	11.5	13	16	10	28	190	110	2.9
402101700500	CD-32	17	16	20	12	32	230	130	4.5
402102510500	CD-36	25.1	20	22	20	36	275	150	6.7

Blueprint

