

Tendeur à deux anneaux DIN 1480

Informations du produit



Tendeur utilisé pour tendre des câbles.

Matériau: Acier Fe-430 b

Marquage: Selon la norme, Marqué CE

Norme: DIN 1480

Attention: Ne pas utiliser pour du levage



Réf.	Longueur mm	Filetage	A mm	B mm	C mm	D mm	E mm	F mm	L1 mm	L2 mm	Poids (kg)
492122600560	140-226	M6	12	110	74	50	10	4	140	226	0,08
492123000560	150-230	M8	15	110	80	52	11	5	150	230	0,14
492127000560	181-270	M10	18	125	97	60	14	6,5	181	270	0,25
492127900560	194-279	M12	21	125	106	67	17	8	194	279	0,37
492133200560	235-332	M14	24	140	126	83	18	8,5	235	332	0,51
492141000560	294-410	M16	27	170	160	97	23	13	294	410	0,95
492148400560	352-484	M20	34	200	190	116	25	14	352	484	1,48
492151600560	368-516	M22	36	220	200	120	30	16	368	516	2,06
492156300560	386-563	M24	39	255	210	125	34	17	386	563	2,76
492160000560	435-600	M27	45	255	236	150	34	18,5	435	600	3,91
492160300560	441-603	M30	45	255	242	150	39	21	441	603	4,05
492162700560	442-627	M33	55	295	242	150	39	21	442	627	5,75
492168100560	498-681	M36	55	295	276	165	49	28	498	681	7,25
492170000560	496-700	M39	63	330	276	165	49	28	496	700	9,36
492176400560	560-764	M42	63	330	320	180	55	40	560	764	14
492176300560	564-763	M45	78	355	322	180	55	40	564	763	19,1
492176300561	564-763	M48	78	355	322	180	55	40	564	763	19,3
492176300562	564-763	M52	78	355	322	180	60	40	564	763	19,3

Dimensions

