

Tendeur anneau et crochet DIN 1480

Informations du produit



Tendeur utilisé pour tendre des câbles.

Matériau: Acier Fe-430 b

Marquage: Selon la norme, Marqué CE

Norme: DIN 1480

Attention: Ne pas utiliser pour du levage



Réf.	Longueur mm	Filetage	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	L1 mm	L2 mm	Poids (kg)
492122600570	140-226	M6	12	110	74	50	10	76	50	8	140	226	0,09
492123500570	155-235	M8	15	110	80	52	11	89	52	10	155	235	0,14
492127300570	185-273	M10	18	125	97	60	14	103	62	13	185	273	0,28
492129000570	208-290	M12	21	125	106	67	17	121	65	17	208	290	0,41
492134400570	248-344	M14	24	140	126	83	18	144	82	14	248	344	0,57
492141900570	303-419	M16	27	170	160	97	23	168	100	16,5	303	419	0,96
492147300570	341-473	M20	34	200	190	116	25	185	110	17	341	473	1,54
492152700570	379-527	M22	36	220	200	120	30	216	125	22	379	527	2,13
492156800570	391-568	M24	39	255	210	125	34	225	125	23	391	568	2,84
492160200570	437-602	M27	45	255	236	150	34	250	146	29	437	602	3,89
492160400570	439-604	M30	45	255	242	150	39	250	140	30	439	604	4,15
492162600570	441-626	M33	55	295	242	150	39	250	140	30	441	626	5,88
492168200570	497-682	M36	55	295	276	165	49	288	170	30	497	682	7,53
492170900570	505-709	M39	63	330	276	165	49	288	170	30	505	709	9,38

Dimensions

